

Concrete Surface Hardener

JTB-201 混凝土起砂处理剂



产 品 说 明 书

Product Manual

产品简介

JTB-201 混凝土起砂处理剂是一种独特配方的水性无机复合液体材料，完全不含有有机物。是专为解决各类混凝土地面起灰，起砂，强度不够等问题而研制的特效产品。

Product

JTB-201 Concrete Surface Hardener is a water-based inorganic composite liquid material with a unique formula, completely free of organic substances. It is a special effect product specially developed to solve various problems such as dusting, sanding and insufficient strength of concrete floors.

introduction

产品特点

Product

features

- 防尘防潮
- 抗渗抗污染
- 耐酸耐碱防油
- 防止起砂
- 施工方便
- 环保无毒



- Dust & moisture resistant
- Waterproof & stain resistant
- Acid, alkali & oil resistant
- Prevents sanding
- Easy to apply
- Eco-friendly & non-toxic

适用范围

Scope of

application

- 起灰起砂的混凝土路（地）面；
- 起灰起砂的水磨石地面；
- 起灰起砂的金刚砂耐磨地面；
- 起灰起砂的水泥自流平地面；
- 起灰起砂水泥砂浆地（墙）面。

Concrete Surface Hardener

JTB-201 混凝土起砂处理剂



产 品 说 明 书

Product Manual

- | | |
|-----------------------------|---|
| 适用范围 | <ul style="list-style-type: none">● Dusting & sanding concrete pavements/floors;● Dusting & sanding terrazzo floors; |
| Scope of application | <ul style="list-style-type: none">● Dusting & sanding quartz hardwearing floors;● Dusting & sanding cement self-leveling floors;● Dusting & sanding cement mortar walls/floors. |

- | | |
|--------------------------------|---|
| 施工工艺 | <ul style="list-style-type: none">● 清理基层: 完全干燥, 清扫灰尘砂石, 去除油漆, 涂料等附着物, 然后用清水冲洗干净, 待地面干燥后即可施工;● 搅拌: 打开JTB-201混凝土起砂处理剂搅拌均匀;● 施工: 用滚筒均匀涂刷地面, 横着一遍竖着一遍, 保证混凝土地面充分均匀的吸收, 也可喷雾器喷洒施工; 渗透快的地方应加大用量; 施工 24 小时后地面即有明显硬化效果。 |
| Construction technology | <ul style="list-style-type: none">● Clean the base layer: Completely dry it, sweep away dust, sand and stones, remove paint, coatings and other attachments, then rinse it clean with water. Construction can be carried out after the ground is dry.● Mixing: Open the JTB-201 Concrete Surface Hardener and stir evenly.● Construction: Apply evenly to the ground with a roller, one coat horizontally and one coat vertically, to ensure the concrete ground is fully and evenly absorbed. It can also be applied by spraying with a sprayer. The dosage should be increased in areas with rapid penetration. The ground shows a significant hardening effect 24 hours after construction. |

Concrete Surface Hardener

JTB-201 混凝土起砂处理剂



产 品 说 明 书

Product Manual

注意事项

本品施工后若地面不在施工其他面层（如：环氧地坪漆，水泥自流平，PVC 地材等）干燥以后即可投入使用。

Precautions

After the application of this product, if no other surface layers (such as epoxy floor paint, cement self-leveling, PVC floor materials, etc.) are applied to the ground, it can be put into use immediately after drying.

包装与储存

20kg/桶、50kg/桶；

宜再室内阴凉、干燥、通风处保存，可在零度以下环境中存放。

保质期：一年。

Packaging and storage

20kg per drum, 50kg per drum;

It should be stored in a cool, dry and well-ventilated indoor place and can be kept in an environment below zero degrees.

Shelf life: One year.

安全规范

本产品含有化工成份，对眼睛及皮肤有刺激，因此请您在施工时穿戴必要的防护工具。

如不慎溅入眼睛，请立即用大量清水清洗，并及时就医。

Safety

specifications

This product contains chemical components and is irritating to eyes and skin. Therefore, please wear necessary protective equipment during construction.

If it accidentally splashes into the eyes, please immediately rinse with plenty of clean water and seek medical attention promptly.



企业公众号

Enterprise Official Account